

# QualiTack<sup>®</sup> 122

Lithium grease MP EP 2

## Description

QualiTack 122 is a lithium grease based on mineral oils. The product contains antioxidants, corrosion inhibitors, extreme pressure and anti-wear additives. It also contains a small amount of polymer to enhance adhesion. The high quality components in this product ensure a long lifetime of both product and equipment.

## Properties

- Very good mechanical stability
- Splendid rust protection
- Good oxidation stability
- Good load carrying capacity

## Application

QualiTack 122 is used in industrial and agriculture applications for the lubrication of low rev. , high load bearings and is suitable for use under the following circumstances: high pressure, high operating temperatures, irregularly shocking and trembling, wet/ dirty and dusty circumstances. QualiTack 122 may also be used for truck-chassis fifth-wheel greasing.



## ISO Norm:

ISO 6743-9; L-XCCIB 2

## DIN Standard:

DIN 51502 KP2K-30

## Approvals:

MAN 283 Li-P2; Mercedes-Benz 267.0

## Technical specifications

Thickener		Lithium 12-HSA
Base oil		Mineral
Colour	Visual	Yellow Brown
Consistency	ASTM D217	NLGI 2
Drop point	IP 396	>180°C
Base oil viscosity @ 40°C	ASTM D 7152	200 mm <sup>2</sup> /s
Base oil viscosity @ 100°C	ASTM D 7152	15 mm <sup>2</sup> /s
4-Ball weld load	DIN 51350	2600 N
Temperature	Continuous period	-30°C – 120°C
Temperature	Short period @ max	130°C