

QualiTack[®] 6215

Calcium Sulphonate Complex



Beschrijving

QualiTack 6215 is een extreem water- en temperatuurbestendig calcium sulfonaat complex vet op basis van minerale basisoliën, met uitstekende hechtende eigenschappen, antioxidanten en corrosie additieven.

Kwaliteitseigenschappen

- Uitstekende roestbescherming
- Uitstekende waterweerstand
- Uitstekende weerstand tegen schokbelasting

Toepassing

QualiTack 6215 is een modern hoge prestatie vet voor smering in de industrie, scheepvaart, offshore en off road. De extreme belastingscapaciteit en extreme waterbestendigheid maken het product bij uitstek geschikt voor zware belastingen met toepassingen in corrosieve-, warme- en vochtige omgeving.

ISO Kwaliteitsnormering: ISO 12924; L-XB(F)DIB1.5

DIN Standaard: DIN 51502; KP1.5N-20

Technische specificaties

Thickener		Calcium Sulfonaat Complex
Base oil		Mineral oil
Colour	Visual	Brown
Consistency	ASTM D217	NLGI 1.5
Drop point	IP 396	>280C°
Base oil viscosity @ 40°C	ASTM D 7152	390 mm ² /s
Base oil viscosity @ 100°C	ASTM D 7152	24 mm ² /s
4-Ball weld load	DIN 51350	6500 N
Water bescherming @90°C	DIN 51807	1
Water uitwas @ 79°C	ISO 11009	<10%
Temperature	Continuous period	-20°C – 140°C
Temperature	Short period @ max	180°C