QualiTack 692 Aluminium Complex Foodgrade

Description

QualiTack 692 is an aluminium complex grease based on medical mineral base oils. The product contains anti-oxidants, corrosion inhibitors, anti-wear and EP additives.

QualiTack 692 is NSF Registered for use in machinery in the food industry where food can come incidental in contact with the grease, category code H1.

Properties

- Good oxidation stability
- Excellent load carrying capacity
- Food machinery product
- Excellent water resistance

Application

QualiTack 692 is mainly used in the canning, dairy and sugar industries, packaging machines, bottle filling machines, fish processing factories and slaughterhouses.







NSF H1

Kosher

Halal



ISO Norm: DIN Standard: ISO 6743-9; L-XBCDB 2 DIN 51502: KP2K-20

Technical specifications

| Thickener | | Aluminium Complex |
|----------------------------|--------------------|--------------------------|
| Base oil | | Pharmaceutical white oil |
| Colour | Visual | White |
| Consistency | ASTM D217 | NLGI 2 |
| Drop point | IP 396 | >230C° |
| Base oil viscosity @ 40°C | ASTM D 7152 | 550 mm ² /s |
| Base oil viscosity @ 100°C | ASTM D 7152 | 53 mm²/s |
| 4-Ball weld load | DIN 51350 | 6000 N |
| Temperature | Continuous period | -20°C – 120°C |
| Temperature | Short period @ max | 130°C |